

管道及管接件技术参数

20°C时以DIN11850标准制造的管道最大工作压力(bar)如下表:

Max . operating pressure (gauge) in bar at 20°C for pipe manufactured acc. to DIN 11850:

SIZE	10	15	20	25	32	40	50	65	80	100	125	150
Serie1	160	105	85	65	55	45	35	55	45	35	30	25
Serie2	220	150	135	100	80	70	50	—	—	—	—	—
Serie3	275	190	160	125	105	90	70	—	—	—	—	—

* 螺纹接头以DIN11851为标准

Screw Connections are made acc .to DIN 11851

在正确使用合适的密封材料条件下, 140°C时以DIN 11851标准制造的螺纹接头最大工作压力(bar)如下表:

Max. operating pressure (gauge) in bar at 140°C for Screw Connections maunfactured acc. to DIN 11851, when correct sealing material is used:

DIN 10-40	30	DIN 50-100	20	DIN 125-150	10
-----------	----	------------	----	-------------	----

* 卡箍接头以DIN32676为标准

Clamp Connections are made acc. to DIN 11851

在正确使用合适的密封材料条件下, 120°C时以DIN 11851标准制造的管夹接头最大工作压力(bar)如下表:

Max. operating pressure (gauge) in bar at 120°C for Clamp Connections maunfactured acc. to DIN 11851, when correct sealing material is used:

DIN 10-50	10	DIN 65-100	8
-----------	----	------------	---

* 法兰连接

Flange connections

在正确使用合适的密封材料条件下, 120°C时法兰连接的最大工作压力(bar)如下表:

Max. operating pressure (gauge) in bar at 120°C for Flange Connections,when correct sealing material is used:

DIN 25-65	16	DIN 80-150	10
-----------	----	------------	----